



The Model T803 CO₂/O₂ Analyzer



The Model T803 CO₂/O₂ analyzer is based on widely accepted sensor techniques, producing an excellent, rugged product designed for extractive CEM or RATA applications. Non-dispersive infrared and paramagnetic measurement technologies give accurate and reliable results combined with product longevity, providing the best price performance value on the market.

— Available with NumaView™ premium T Series software —

- Large, vivid, and durable color touchscreen display
- All other T Series instrument platform features
- Lifetime technical support by phone and email
- Standard two-year warranty

Model T803 Specifications

<ul style="list-style-type: none"> ■ CO₂ Range ■ O₂ Range 	0 - 20% full scale (selectable, dual-range supported) 0 - 1% to 0-100%
<ul style="list-style-type: none"> ■ Zero Noise 	< 0.02% (RMS)
<ul style="list-style-type: none"> ■ Span Noise 	< 0.1% of reading (RMS)
<ul style="list-style-type: none"> ■ Lower Detectable Limit 	< 0.04%
<ul style="list-style-type: none"> ■ Zero Drift 	< ±0.02% /24 hours; < ±0.05% /7 days
<ul style="list-style-type: none"> ■ Span Drift 	< ±0.1% /7 days
<ul style="list-style-type: none"> ■ Accuracy: 	< ±(1.5% of range +2% of reading)
<ul style="list-style-type: none"> ■ Temperature Coefficient: 	< ±0.01% per degree C
<ul style="list-style-type: none"> ■ O₂ Ranges 	Min: 0 - 1% full scale (selectable) Max: 0 - 100% full scale (selectable)
<ul style="list-style-type: none"> ■ Linearity 	±0.1%
<ul style="list-style-type: none"> ■ Rise and Fall Time: 	< 60 seconds to 95%
<ul style="list-style-type: none"> ■ Flow Rate 	120ml ± 20ml/min
<ul style="list-style-type: none"> ■ Humidity Range: 	0 - 95% RH
<ul style="list-style-type: none"> ■ Pressure Range: 	25 - 31 in Hg
<ul style="list-style-type: none"> ■ Power Requirements 	100V-120V, 220V-240V, 50/60 Hz
<ul style="list-style-type: none"> ■ Analog Output Ranges 	10V, 5V, 1V, 0.1V (selectable)
<ul style="list-style-type: none"> ■ Recorder Offset 	±10%
<ul style="list-style-type: none"> ■ Included I/O 	1 x Ethernet: 10/100Base-T 2 x RS232 (300-115,200 baud) 2 x USB device ports 8 x opto-isolated digital outputs 6 x opto-isolated digital inputs 4 x analog outputs
<ul style="list-style-type: none"> ■ Optional I/O 	1 x USB com port 1 x RS485 8 x analog inputs (0-10V, 12-bit) 4 x digital alarm outputs Multidrop RS232 3 x 4-20mA current outputs
<ul style="list-style-type: none"> ■ Operating Temperature Range 	5 - 40°C
<ul style="list-style-type: none"> ■ Dimensions (HxWxD) 	7" x 17" x 23.5" (178 x 432 x 597 mm)
<ul style="list-style-type: none"> ■ Weight 	28 lbs (12.7 kg)

Specifications subject to change without notice.
All specifications are based on constant conditions.



TELEDYNE API
Everywhere you look™

9970 Carroll Canyon Road ■ San Diego, CA 92131

Ph. 858-657-9800 Fax 858-657-9816

Email api-sales@teledyne.com

© 2017 Teledyne API

Printed documents are uncontrolled. SAL000067C
(DCN 7436) 03.13.17

Gas-Detection

LAUPER
INSTRUMENTS

Lauper Instruments AG
Irisweg 16B
CH-3280 Murten
Tel. +41 26 672 30 50
info@lauper-instruments.ch
www.lauper-instruments.ch

