



Detect up to five gases simultaneously with the rugged, wireless, Ventis® Pro5 Multi-Gas Monitor. With Ventis Pro5, safety goes beyond the gas detector whether you need team-based alarm sharing, remote monitoring with location details, or both. The monitor is also backed by a Guaranteed for Life™ warranty.

- Eliminate the need for two pieces of equipment by using Ventis Pro5 for personal monitoring and confined space entry.
- Train workers on one, multi-purpose gas monitor and reduce the risk and investment of having different devices in the field.
- Improve team and site safety by locally sharing alarms and gas readings between wirelessly connected Ventis Pro5 monitors.
- Get real-time location and alarm data directly from Ventis Pro5 gas monitors to a designated safety contact with the optional cellular or wi-fi battery pack.
- Reinforce safe behavior with programmable alarm action messages like “EVACUATE” or “VENTILATE” based on alarm level.
- Simplify the user experience with the ability to hide unnecessary screens based on user needs, role, industry, or site.

Sensor & Configuration Options

The Ventis Pro5 offers sensor and configuration options for multiple industries and applications, including standard and non-standard 4-gas, 5-gas, and a methane IR sensor, making it a cost-effective option for personal protection and confined space applications.

LEL (CH ₄ % Vol)	CO	IR CO ₂	HCN
LEL (Methane)	CO/H ₂ Low	IR CO ₂ /CH ₄	NH ₃
LEL (Pentane)	CO/H ₂ S	IR CO ₂ /LEL	PH ₃
O ₂	SO ₂	IR HC	PID
H ₂ S	NO ₂	ULP IR CH ₄	
Cl ₂	IR CH ₄	ULP IR HC	

**INDUSTRIAL
SCIENTIFIC**

SPECIFICATIONS*

WARRANTY

Guaranteed for Life™. Warranted for as long as the instrument is supported by Industrial Scientific Corporation (Excludes sensors, batteries, and filters). Pump and O₂, LEL, CO, and H₂S sensors warranted for four years. PID sensor warranted for one year. All other sensors and batteries are warranted for two years.

KEYPAD

Two buttons for operation. Dedicated panic button.

DATA LOG

At least 3 months at 10-second intervals

EVENT LOGGING

60 alarm events

INGRESS PROTECTION

IP68 (submersion at 1.5 meters for 1 hour)

CASE MATERIAL

Polycarbonate with protective rubber overmold

DIMENSIONS

104 x 58 x 36 mm (4.1 x 2.3 x 1.4 in) without Pump
172 x 67 x 65 mm (6.8 x 2.6 x 2.6 in) with Pump
104 x 58 x 61 mm (4.1 x 2.3 x 2.4 in) with wi-fi and cellular battery

WEIGHT

200 g (7.05 oz) typical, without Pump
390 g (13.76 oz) typical, with Pump
243 g (8.5 oz) typical, with wi-fi battery
247 g (8.7 oz) typical, with cellular battery

HUMIDITY RANGE

15% to 95% non-condensing (continuous)

TEMPERATURE RANGE

-40 °C to 50 °C (-40 °F to 122 °F) **

DISPLAY/READOUT

Backlit liquid crystal display (LCD)

POWER SOURCE/RUN TIME

Rechargeable Slim Extended Lithium-ion battery (no Pump option)
(18 hours typical @ 20 °C) with LEL
(54 hours typical @ 20 °C) with IR

Rechargeable Lithium-ion battery (no Pump option)
(12 hours typical @ 20 °C) with LEL
(36 hours typical @ 20 °C) with IR

Rechargeable Extended-Range Lithium-ion battery with LEL
(23 hours typical @ 20 °C) without Pump
(18 hours typical @ 20 °C) with Pump

Rechargeable Extended-Range Lithium-ion battery with IR
(72 hours typical @ 20 °C) without Pump
(32 hours typical @ 20 °C) with Pump

Rechargeable wi-fi Lithium-ion battery (no Pump option)
(14 hours typical @ 20 °C) with LEL

Rechargeable Cellular Lithium-ion battery (no Pump option)
(14 hours typical @ 20 °C) with LEL

Learn More about the Ventis Pro5:
www.indsci.com/ventispro

SPECIFICATIONS*

ALARMS

Four visual alarm LEDs (two red, two blue);
95 decibel (dB) audible alarm at a distance of 10 cm (3.94 in);
Vibration alarm

SENSORS

Combustible Gases/Methane – Catalytic Bead
O₂, CO, CO/H₂ low, H₂S, HCN, NH₃, NO₂, PH₃, SO₂, Cl₂ – Electrochemical
CO₂, CH₄, CO₂/LEL, CO₂/CH₄, HC – Infrared, PID, ULP IR CH₄, ULP IR HC

MEASURING RANGES

CATALYTIC BEAD
Combustible Gases: 0-100% LEL in 1% increments
Methane (CH₄): 0-5% of vol in 0.01% increments

ELECTROCHEMICAL
Ammonia (NH₃): 0-500 ppm in 1 ppm increments
Carbon Monoxide (CO): 0-2,000 ppm in 1 ppm increments
Carbon Monoxide (CO/H₂ low): 0-1,000 ppm in 1 ppm increments
Carbon Monoxide/Hydrogen Sulfide: CO: 0-1,500 ppm in 1 ppm increments
H₂S: 0-500 ppm in 0.1 ppm increments
Chlorine (Cl₂): 0-50 ppm in 0.1 ppm increments
Hydrogen Sulfide (H₂S): 0-500 ppm in 0.1 ppm increments
Hydrogen Cyanide (HCN): 0-30 ppm in 0.1 ppm increments
Nitrogen Dioxide (NO₂): 0-150 ppm in 0.1 ppm increments
Oxygen (O₂) (Standard/Long-Life): 0-30% of vol in 0.1% increments
Phosphine (PH₃): 0-10 ppm in 0.01 ppm increments
Sulfur Dioxide (SO₂): 0-150 ppm in 0.1 ppm increments

INFRARED
Carbon Dioxide (CO₂): 0-5% vol in 0.01% increments
Methane (CH₄): 0-5% vol in 0.01% increments
5-100% vol in 0.1% increments
Carbon Dioxide/Combustible CO₂: 0-5% vol in 0.01% increments
LEL: 0-100% LEL in 1% increments
Carbon Dioxide/Methane: CO₂: 0-5% vol in 0.01% increments
CH₄: 0-5% vol in 0.01% increments
CH₄: 5-100% vol in 0.1% increments
Hydrocarbons 0-100% LEL in 1% increments
Hydrocarbon (HC ULP) 0-100% LEL in 1% increments
Methane (CH₄ ULP) 0-100% LEL in 0.1% increments
5.1-100% vol in 0.1% increments

PHOTOIONIZATION
Volatile Organic Compounds (10.6 eV) 0-2,000 ppm in 0.1 ppm increments

CERTIFICATIONS

INGRESS PROTECTION IP68
ANZEx: Ex ia I Ma/Ex ia IIC T4 Ga, -40 °C ≤ Ta ≤ 50 °C
Ex d ia I Mb/Ex d ia IIC T4 Gb IR sensor, -20 °C ≤ Ta ≤ 50 °C IR sensor
ATEX: Equipment Group and Category II 1G, Ex ia IIC, Ga, T4
Equipment Group and Category II 2G, Ex d ia IIC, Gb, T4, IR sensor
China CPC: CPA 2017-C103
China Ex: Ex ia IIC T4 Ga, -40 °C ≤ Ta ≤ 50 °C; Ex d ia IIC T4 Gb IR sensor,
-20 °C ≤ Ta ≤ 50 °C IR sensor
CSA: CI I, Div 1, Gr A-D, T4; CI I, Zone 1, Ex d ia IIC, T4 | C22.2
No. 152 for % LEL reading only | 70046111
IECEX: CI I, Zone 0, Ex ia IIC, Ga, T4; CI I, Zone 1, Ex d ia IIC, Gb, T4, IR sensor
INMETRO: Ex ia IIC T4 Ga, -40 °C ≤ Ta ≤ 50 °C
Ex d ia IIC T4 Gb IR sensor, -20 °C ≤ Ta ≤ 50 °C IR sensor
KC: Ex d ia IIC T4
MSHA: 30 CFR Part 22; Permissible for underground mines
NCC: NCC/TSNI/WN/TA/CERT/3139/2019
PA-DEP: BFE 46-12 Permissible for PA Bituminous underground mines
UL: CI I, Div 1, Gr A-D, T4; CI II, Div 1, Gr E-G, T4
CI I, Zone 0, AEx ia IIC, T4; CI I, Zone 1, AEx d ia IIC, T4, IR sensor

See www.indsci.com/ventispro for the product manual with the full certification list.

LANGUAGE

English, French, Spanish, German, Italian, Dutch, Portuguese, Polish

SUPPLIED WITH MONITOR

Calibration Cup (without Pump), Sample Tubing (with Pump), Reference Guide

COMMUNICATIONS

Lens™ Wireless Mesh Network	Frequency: ISM license-free band (2.405 - 2.480 GHz)
	Max Peers: 25 devices per network group
	Range: 100 m (300 ft) line of sight, face-to-face
	Encryption: AES-128
Cellular	United States: LTE CAT M1 (AT&T, Verizon)
	Canada: LTE CAT M1 (Bell, Rogers, Telus)
	EMEA: LTE CAT M1 (Tele2)
	UAE: LTE CAT M1 (Etisalat - E&)
Wi-fi	802.11 b/g/n 2.4GHz wi-fi with WPA2 security

CERTIFICATIONS

AMERICAS	EUROPE	***UAE
Cellular: FCC, ISCED – Canada, PTCRB, AT&T and Verizon	Cellular: Radio Equipment Directive (R.E.D.)	Cellular: TDRA
Wi-fi: FCC, ISCED – Canada	Wi-fi: Radio Equipment Directive (R.E.D.)	Wi-fi: TDRA
LENS: FCC, ISCED – Canada	LENS: Radio Equipment Directive (R.E.D.)	LENS: TDRA

* These specifications are based on performance averages and may vary by instrument.

** Operating temperatures above 50 °C (122 °F) may cause reduced instrument accuracy. Operating temperatures below -20 °C (-4 °F) may cause reduced instrument accuracy and affect display and alarm performance. See Product Manual for details.

*** Coming soon


† Contact sales representative for country-specific wireless approvals and certifications.



INDUSTRIAL
SCIENTIFIC

www.indsci.com

REV 5 0623



Lauper Instruments AG

Irisweg 16 B

CH-3280 Murten

Tel. +41 26 672 30 50

info@lauper-instruments.ch

www.lauper-instruments.ch